

# **Safety Data Sheet**Carbon Dioxide, Liquid Refrigerated

#### Sidney Lee Welding Supply

2247 Highway US 19-41 Hampton, GA 30228 http://www.sidneylee.com

CHEMTREC - 24HR Emergency Contact 1-800-424-9300 ACCT: 20182

### Section 1: Product and Company Identification

**Sidney Lee Welding Supply** 

2247 Highway US 19-41 Hampton, GA 30228 http://www.sidneylee.com

CHEMTREC - 24HR Emergency Contact 1-800-424-9300 ACCT: 20182

Product Code: Carbon Dioxide, Liquid Refrigerated

### Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated

**Precautionary Statements** 

#### Storage:

Protect from sunlight. Store in well-ventilated place.

### Section 3: Composition/Information on Ingredients

**CAS** # 124-38-9

Chemical Substance	Chemical Family	Trade Names		
CARBON DIOXIDE, LIQUID	Inorganic gases	Carbon dioxide (cryogenic liquid), LCO2, liquefied CO2		

### Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Do not induce vomiting.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

### Section 5: Fire Fighting Measures

Products of Combustion	Protection of Firefighters	
Non-flammable	Non-flammable	

### Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch spilled material.	Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Keep out of water supplies and sewers.	Stop leak if possible without personal risk.

Methods for Cleanup	Other Information
Stop leak, evacuate.	None

### Section 7: Handling and Storage

Handling	Storage
Store and use with adequate ventilation. Firmly secure cylinders upright to	Do not get liquid in eyes, on skin, or clothing. Protect cylinders
keep them from falling or being knocked over. Screw valve protection cap	from damage. Use a suitable hand truck to move cylinders; do not
firmly in place by hand. Store only where temperature will not exceed 125 F	drag, roll, slide, or drop. Open valve slowly. Close cylinder valve
(52 C). Store full and empty cylinders separately. Use a first-in, first-out	after each use; keep closed even when empty. If valve is hard to
inventory system to prevent storing full cylinders for long periods.	open, discontinue use and contact your supplier

### Section 8: Exposure Controls/Personal Protection

Exposure Guidelines
OSHA PEL 5,000 ppm ACGIH TLV-TWA (2009) 5,000 ppm; 30,000 ppm, 15 min STEL

#### **Engineering Controls**

Handle only in fully enclosed systems.

Eye Protection	Skin Protection	Respiratory Protection
, , , , , , , , , , , , , , , , , , , ,	Wear appropriate protective, cold insulating clothing.	Non-flammable

#### General Hygiene considerations

- -Avoid breathing vapor or mist
- -Avoid contact with eyes and skin
- -Wash thoroughly after handling and before eating or drinking

### Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Liquid	Colorless	Colorless	N/A	Liquid	Odorless	Acid taste

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Not flammable	Not available	N/A	Nonflammable	Nonflammable	Nonflammable

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pН	Odor Threshold	Evaporation Rate	Viscosity
Not available	-71 F (-57 C) @ 4000 mmHg	43700 mmHg @ 21 C	1.5 (Air=1)	1.522 @ 21 C	Soluble	3.7 (saturated aqueous solution) @ 101.3 kPa (carbonic acid)	Not available	Not applicable	0.01657 cP @ 0 C

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
44.01	C-02	0.114	Not available	Not applicable	Not applicable	Soluble: Alcohol, acetone, hydrocarbons, organic solvents

### Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Stable at normal temperatures and	Stable at normal temperatures and	Oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases, Alkali metals, alkaline earth metals, metal acetylides, chromium, titanium above 1022 F (550 C), uranium
pressure.	pressure.	above 1382 F (750 C), magnesium above 1427 F (775 C)

Hazardous Decomposition Products	Possibility of Hazardous Reactions
Carbon monoxide	Will not polymerize.

### Section 11: Toxicology Information

#### Acute Effects

Oral LD50	Dermal LD50	Inhalation
Not established	Not established	Ringing in the ears, nausea, irregular heartbeat, headache, drowsiness, dizziness, tingling sensation, visual disturbances, suffocation, convulsions, coma

<b>Eye Irritation</b>	Skin Irritation	Sensitization
Irritation, frostbite, blurred vision		Asphyxiant OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION CGA -HG01 - MAY CAUSE FROSTBITE CGA - HG03 - MAY INCREASE RESPIRATION AND HEART RATE

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not available	Not established	Available.	No data

### Section 12: Ecological Information

Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: 150000 ug/L 48 day(s) (Mortality) Brown trout (Salmo trutta) Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Moderately volatile from water.	Accumulates very little in the bodies of living organisms.	Leaches through the soil

### Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations.

### Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Carbon dioxide	UN2187	2.2	Not applicable	Nonflammable gas	75 kg or L	150kg	None

Canadian Transportation of Dangerous Goods

Shipping Name	UN Number	Class	Packing Group / Risk Group
Carbon dioxide	UN2187	2.2	Not applicable

### Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
Not regulated.	Not regulated.	Not regulated.

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	No	No	Yes

SARA 372.65

Not regulated.

**OSHA Process Safety** 

Not regulated.

State Regulations

CA Proposition 65
Not regulated.

Sidney Lee Welding Supply Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

#### Canadian Regulations

WHMIS Classification
Α

National Inventory Status

US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)	
Listed on inventory.	Not listed.	Listed on inventory.	

## Section 16: Other Information

NFPA Rating	
HEALTH=3 FIRE=0 REACTIVITY=0 SPECIAL=SA	

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard