



Safety Data Sheet

Heptane

Sidney Lee Welding Supply
2247 Highway US 19-41
Hampton, GA 30228
<http://www.sidneylee.com>

CHEMTREC - 24HR Emergency Contact
1-800-424-9300
ACCT: 20182

Section 1: Product and Company Identification

Sidney Lee Welding Supply
2247 Highway US 19-41
Hampton, GA 30228
<http://www.sidneylee.com>

CHEMTREC - 24HR Emergency Contact
1-800-424-9300
ACCT: 20182

Product Code: Heptane

Section 2: Hazards Identification



Danger

Hazard Classification:

Acute Aquatic Toxicity (Category 1)
Aspiration Hazard (Category 1)
Chronic Aquatic Toxicity (Category 1)
Flammable (Category 1)
Gases Under Pressure
Specific target organ toxicity (Single Exposure) (Category 3)

Hazard Statements:

Contains gas under pressure; may explode if heated
Extremely flammable gas
May be fatal if swallowed and enters airways
May cause respiratory irritation;
Very toxic to aquatic life
Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use only outdoors or in a well-ventilated area.

Avoid breathing dust/fume/gas/mist/ vapors/spray.
 [In case of inadequate ventilation] wear respiratory protection.

Response:

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 Immediately call a poison center or doctor.
 Eliminate all ignition sources if safe to do so.
 Do NOT induce vomiting.
 If swallowed: Rinse mouth. Do NOT induce vomiting.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
 Protect from sunlight.
 Store locked up.

Disposal:

Dispose of contents and/or container in accordance with applicable regulations.

Section 3: Composition/Information on Ingredients

CAS #
142-82-5

Chemical Substance	Chemical Family	Trade Names
n-HEPTANE	Hydrocarbons, Aliphatic, Saturated	NORMAL HEPTANE; DIPROPYL METHANE; HEPTYL HYDRIDE; DIPROPYLMETHANE; N-HEPTANE; UN 1206; C7H16

Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.	Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Aspiration hazard. DO NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get immediate medical attention. Give artificial respiration if not breathing.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.	Not Available

Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Regular dry chemical, carbon dioxide, water, regular foam Large fires: Use regular foam or flood with fine water spray.	Irritating, toxic gases	-Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode. -Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard area and deny entry.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.

Methods for Cleanup	Other Information
Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. Remove	None

Section 7: Handling and Storage

Handling	Storage
Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines
HEPTANE: n-HEPTANE: 500 ppm (2000 mg/m ³) OSHA TWA 400 ppm (1640 mg/m ³) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 500 ppm (2050 mg/m ³) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 85 ppm (350 mg/m ³) NIOSH recommended TWA 10 hour(s) 440 ppm (1800 mg/m ³) NIOSH recommended ceiling 15 minute(s) HEPTANE, ALL ISOMERS: 400 ppm ACGIH TWA 500 ppm ACGIH STEL

Engineering Controls

Handle only in fully enclosed systems.

Eye Protection	Skin Protection	Respiratory Protection
Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Liquid	Clear	Colorless	N/A	Volatile liquid	Faint odor, gasoline odor	N/A

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
25 F (-4 C) (CC)	IB	Not available	399 F (204 C)	0.067	0.0105

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
208 F (98 C)	-132 F (-91 C)	40 mmHg @ 20 C	3.45 (Air=1)	0.6837	0.005%	Not available	220 ppm	2.80 (butyl acetate=1)	Not available

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
100.21	C-H3-(C-H2)5-C-H3	Not available	Not available	Not available	1	Soluble: Ethanol, ether, chloroform, acetone

Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, combustible materials

Hazardous Decomposition Products	Possibility of Hazardous Reactions
Oxides of carbon	Will not polymerize.

Section 11: Toxicology Information

Acute Effects

Oral LD50	Dermal LD50	Inhalation
103 gm/m3/4 hour(s) inhalation-rat LC50	Not available	Irritation, loss of appetite, headache, drowsiness, dizziness, emotional disturbances, loss of coordination, suffocation, unconsciousness

Eye Irritation	Skin Irritation	Sensitization
Irritation	Irritation	Aspiration hazard, Category 1; H304: May be fatal if swallowed and enters airways. Skin irritation, Category 2; H315: Causes skin irritation. Specific Target Organ Toxicity (single exposure), Category 3; H336: May cause drowsiness or dizziness. Hazardous to the aquatic environment, Acute Category 1; H400: Very toxic to aquatic life. Hazardous to the aquatic environment, Chronic Category 1; H410: Very toxic to aquatic life with long lasting effects.

Chronic Effects

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not available	Not available	Not available	No data

Section 12: Ecological Information

Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: Acute LC50 4924000 ug/L Fresh water Fish - Western mosquitofish - Gambusia affinis - Adult 96 hours; 375000 ug/L 96 hour(s) LC50 (Mortality) Mozambiqu Invertebrate toxicity: 2500000 ug/L 96 hour(s) LC50 (Mortality) Oligochaete (Branchiura sowerbyi) Algal toxicity: 1500 ug/L 8 year(s) EC50 (Photosynthesis) Algae, phytoplankton, algal mat (Algae) Phyto toxicity: Not available Other toxicity: Not available	Harmful to aquatic life.	Not available	Not available

Section 13: Disposal Considerations

Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Heptanes	UN1206	3	II	3	N/A	N/A	N/A

Canadian Transportation of Dangerous Goods

Shipping Name	UN Number	Class	Packing Group / Risk Group
Heptanes	UN1206	3	II

Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
Not regulated.	Not regulated.	Not regulated.

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	Yes	No	No

SARA 372.65

Not regulated.

OSHA Process Safety

Not regulated.

State Regulations

CA Proposition 65
Not regulated.

Canadian Regulations

WHMIS Classification
B2 D2B

National Inventory Status

US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Listed on inventory.	HEPTANE CAS NUMBER: 142-82-5 SECTION 4	Not determined.

Section 16: Other Information

NFPA Rating
HEALTH=2 FIRE=3 REACTIVITY=0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard